



## The universal Label Dispenser HS 150 with label counter

Made in Germany.

# Label Dispenser HS 150

## With label counter



All current adhesive labels are being dispensed fast and easy with the Label Dispenser HS 150. After removing the label the next one is brought into position automatically.

The built-in counter indicates the number of labels already taken.

The label size is adjusted with the rotatable micro switch. If the labels are longer the front side is dispensed first. After removal of the label the micro switch is released and the rest of the label is removed easily with the rewinding of the liner.

The shape of the labels is optional. They can be punched or cut without gap. For round or oval labels the micro switch is moved sideways up to the front edge of the label.

With the powerful rewinding motor rolls are wound inside or outside up to 240 mm diameter and processed to a width up to 150 mm.

## Technical Data

<b>Material</b>	
Label width mm	12 up to 150
Label length mm	min. 15, max 300
Roll diameter max. mm	240
Label rewinding	inside or outside
Core diameter min. mm	40
Winding diameter for liner up to mm	100
Feed supply rate mm/sec.	40 up to 100
<b>Handling</b>	
Justification label length	micro switch
Volume display	4 digits, increasing
Key	Reset - to clock the volume display
Switch	Power „ON - OFF“
<b>Electrical Data</b>	
Power supply	220/230 Volt +6/-10%, 50 Hz 110 Volt +6/-10%, 60 Hz
Connection	Power plug
<b>Dimensions</b>	
Height x Width x Depth mm	188 x 250 x 240
Weight kg	4,4
<b>Operation data</b>	
Operation temperature	10 up to 35 °C
Storage- and transport temperature	-20 up to 50°C
Humidity	30 up to 85 % not condensing
Noise	< 60 dB (A)
Licenses	DIN VDE 0805
Suppression of interference	DIN VDE 0871 cam B Protection class 1
Degree of protection	IP 20 in compliance with UL-Standard

[www.cab.de](http://www.cab.de)

### Germany

cab Produkttechnik  
GmbH & Co KG  
Postfach 1904  
76007 Karlsruhe  
Wilhelm-Schickard-Str. 14  
76131 Karlsruhe  
Telefon +49 721 6626-0  
Telefax +49 721 6626-249  
[www.cab.de](http://www.cab.de)  
[info@cab.de](mailto:info@cab.de)

*Representatives in other countries on request.*

### France

cab technologies s.a.r.l.  
67350 Niedermodern  
Téléphone +33 388 722 501  
[www.cab.de/fr](http://www.cab.de/fr)  
[info.fr@cab.de](mailto:info.fr@cab.de)

### USA

cab Technology Inc.  
Tyngsboro MA, 01879  
Phone +1 978 649 0293  
[www.cab.de/us](http://www.cab.de/us)  
[info.us@cab.de](mailto:info.us@cab.de)

### South Africa

cab Technology (Pty.) Ltd.  
2125 Randburg  
Phone +27 11-886-3580  
[www.cab.de/za](http://www.cab.de/za)  
[info.za@cab.de](mailto:info.za@cab.de)

### Asia 亚洲

cab Technology Co, Ltd.  
希爱比科技股份有限公司  
Junghe, Taipei, Taiwan  
Phone +886 2 8227 3966  
[www.cab.de/tw](http://www.cab.de/tw)  
[info.asia@cab.de](mailto:info.asia@cab.de)

### China 中国

cab (Shanghai) Trading Co., Ltd  
铠博(上海)贸易有限公司  
Phone +86 21 6236-3161  
[www.cab.de/cn](http://www.cab.de/cn)  
[info.cn@cab.de](mailto:info.cn@cab.de)

*This documentation and any translations hereof are the property of cab GmbH & Co KG.*

*The replication, processing, reproduction or distribution in whole or in parts requires our prior written consent. © Copyright by cab.*

*All specifications on delivery, design and technical data are compiled to the best of our current knowledge and are subject to change without prior notice.*